

# Lautsprecher

## HMX 8.8 S-LD-SW.2

224 (8.8) mm (in.) | 123 (4.84) mm (in.) | Hi-end Led Coax | 200 W | 4 Ohm

The **HMX 8.8 S-LD-SW.2** is designed for those who seek **maximum acoustic impact combined with refined aesthetics**, delivering powerful sound performance with a clean and elegant look on board. This version features the **Silver White sport grille**, ideal for premium boats, bright interiors, and sophisticated deck layouts, ensuring seamless visual integration with modern marine design. The new **SPORT.2** generation introduces a **redesigned central element with parametric mesh grille**, enhancing both style and acoustic transparency. At the core of the upgrade is the **completely re-engineered crossover**, delivering a more exciting, dynamic, and immersive sound experience, with improved clarity and output even in open-air conditions. The larger **8.8" woofer** provides deeper and more impactful low-frequency performance, making it the perfect choice for those who want a fuller, more powerful sound on board. Built with marine-grade materials – including **UV- and salt-resistant ASA grille, polypropylene cone, and Santoprene™ surround** – the HMX SPORT.2 ensures long-term durability and reliability in the harshest marine environments. The integrated **RGB LED lighting** allows full customization of the onboard atmosphere, perfectly matching any vessel style.



### TECHNICAL SPECS

|                              |                                            |
|------------------------------|--------------------------------------------|
| Component                    | HI-END LED COAX                            |
| Size                         | 224 (8.8) mm (in.)                         |
| Power Handling - Continuous  | 100 W                                      |
| Power Handling - Peak        | 200 W                                      |
| Impedance                    | 4 Ohm                                      |
| Depth                        | 123 (4.84) mm (in.)                        |
| Tweeter diaphragm            | 36 (1.4) mm (in.)                          |
| Woofer Voice Coil Ø          | 32 (1.26) mm (in.)                         |
| Tweeter Voice Coil Ø         | 20 (0.8) mm (in.)                          |
| Frequency Response           | 45 ÷ 25k Hz                                |
| Woofer Magnet size D x d x h | 90 x 40 x 20 (3.54 x 1.57 x 0.79) mm (in.) |
| Tweeter Magnet size D x h    | 19,7 x 3 (0.78 x 0.12) mm (in.)            |
| Weight of one speaker        | 1,66 (3.66) kg (lb.)                       |
| Woofer Magnet                | High density flux ferrite                  |
| Tweeter Magnet               | Neodymium                                  |
| Cone                         | Polypropylene with UV inhibitors           |
| Dome                         | PEI                                        |

All the specifications subject to change without notice\_20\_A

|       |                      |
|-------|----------------------|
| Xmech | ±8,5 (0.33) mm (in.) |
|-------|----------------------|

## ELECTRIC-ACOUSTIC SPECS

|     |           |
|-----|-----------|
| D   | 174 mm    |
| Re  | 3,1 Ohm   |
| Fs  | 50 Hz     |
| Le  | 0,52 mH   |
| Vas | 29,46 l   |
| Mms | 27,3 g    |
| Cms | 0,37 mm/N |
| BL  | 6,6 T*m   |
| Qts | 0,58      |
| Qes | 0,61      |
| Qms | 11        |
| Spl | 91 dB     |

## PHYSICAL SPECS

## FREQUENCY RESPONSE